

SCREW AIR COMPRESSOR TECHNICAL SPECIFICATIONS

LUPAMAT LKV 22/13 DHK PLUS

DESCRIPTION	SPECIFICATIONS
Compressor Type	Oil Injected Screw Air Compressor
Max. Pressure	13 bar
Free Air Delivery (at 13 bar)	* 2,6 m ³ /min.
Min. Pressure	5 bar
Min. Free Air Delivery	0,6 m ³ /min.
Shaft Power(at 13 bar)	22 kW
Max. Ambient Temperature	40 ^o C
Electric Motor	22 kW / 30 hp ; 2 Pole (2960 rpm); 400V; 50Hz; IP55; F Insulation; B35 Built; IE3 Class
Cooling System	Air Cooling with Axial Fan
Fan Motor & Capacity	0,46 kW; (1365 rpm); 400V; 50Hz --- 4800/125 (m ³ /h)/Pa
Airend	SCA10 – TMC(ITALY)
Hydraulic Connections	VITILLO(ITALY)
Cooler	AKG(GERMANY) / CIESSE(ITALY)
Oil & Air Filters	MANN+HUMMEL(GERMANY)
Suction Control Group	HOERBIGER(GERMANY)
Electric Components	SCHNEIDER(FRANCE) / MITSUBISHI(JAPAN)
Variable Frequency Drive(VFD)	MITSUBISHI(JAPAN)
Coupling	DODGE / REXNORD(USA)
R.P.M of Airend	3470 rpm
Driving	Direct Driven with Frequency Controller
Outlet Connection & Cable Size	1 – (3x16)+10 mm ²
Length	1400 mm
Width	1000 mm
Height	1335 mm
Weight	800 kg
Noise Level	**70 dB (A) Tolerance \pm 3 dB (A)
Max. Oil Content	2-3 ppm.(mg/ m ³ /h)
Warranty	Two Years Against Manufacturing Defects
Shipping Weight & Dimension	850 kg – 1500 x 1100 x 1485 mm

* FAD performance measured according to ISO 1217, Annex E-2009

** Noise Level measured to ISO 2151, Tolerance \pm 3 dB (A)

†Lupamat reserves the right to make alterations on given data & compressor design without prior notice.

Lupamat

Makina Sanayii A.Ş.

