

## SCREW AIR COMPRESSOR TECHNICAL SPECIFICATIONS

### LUPAMAT LKV 15/8 DHK PLUS

DESCRIPTION	SPECIFICATIONS
<b>Compressor Type</b>	Oil Injected Screw Air Compressor
<b>Max. Pressure</b>	8 bar
<b>Free Air Delivery (at 8 bar)</b>	* 2,3 m <sup>3</sup> /min.
<b>Min. Pressure</b>	5 bar
<b>Shaft Power (at 8 bar)</b>	15 kW
<b>Max. Ambient Temperature</b>	40°C
<b>Electric Motor</b>	15 kW / 20 hp ; 2 Pole (2945 rpm); 400V; 50Hz; IP55; F Insulation; B35 Built ; IE3 Class
<b>Cooling System</b>	Air Cooling with Axial Fan
<b>Fan Motor &amp; Capacity</b>	0,25 kW; (1400 rpm); 400V; 50Hz --- 3750/100 (m <sup>3</sup> /h)/Pa
<b>Airend</b>	SCA9-TMC(ITALY)
<b>Hydraulic Connections</b>	VITILLO(ITALY)
<b>Cooler</b>	AKG(GERMANY)
<b>Oil &amp; Air Filters</b>	MANN+HUMMEL(GERMANY)
<b>Suction Control Group</b>	VMC(ITALY)
<b>Electric Components</b>	SCHNEIDER(FRANCE) / MITSUBISHI(JAPAN)
<b>Variable Frequency Drive(VFD)</b>	MITSUBISHI(JAPAN)
<b>Coupling</b>	DODGE / REXNORD(USA)
<b>R.P.M of Airend</b>	4278 rpm
<b>Driving</b>	Direct Driven with Frequency Controller
<b>Outlet Connection &amp; Cable Size</b>	¾" – (3 x 10)+6+6 mm <sup>2</sup>
<b>Length</b>	1300 mm
<b>Width</b>	760 mm
<b>Height</b>	1225 mm
<b>Weight</b>	680 kg
<b>Noise Level</b>	**67 dB (A)
<b>Max. Oil Content</b>	2-3 ppm.(mg/m <sup>3</sup> )
<b>Warranty</b>	Two Years Against Manufacturing Defects
<b>Shipping Weight &amp; Dimension</b>	730 kg –1400 x 860 x 1375 mm.

\* FAD performance measured according to ISO 1217,Annex E-2009

\*\* Noise Level measured to ISO 1217, Tolerance ± 3 dB (A)

Lupamat reserves the right to make alterations on given data & compressor design without prior notice.

# Lupamat

Makina Sanayii A.Ş.

